

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
20 January 2005 (20.01.2005)

PCT

(10) International Publication Number
WO 2005/006657 A1

(51) International Patent Classification⁷: **H04L 12/28**,
12/56

(21) International Application Number:
PCT/AU2004/000941

(22) International Filing Date: 14 July 2004 (14.07.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2003903602 14 July 2003 (14.07.2003) AU

(71) Applicant and

(72) Inventor: MUTABAZI, Steven, Luzima [AU/AU]; 57
Burnett Street, Mitcham, VIC 3132 (AU).

(74) Agent: COLLISON & CO; GPO Box 2556, Adelaide,
S.A. 5001 (AU).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,

AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.


(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,
SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: NETWORKING CORRIDORS FOR PACKET DATA AND VOICE COMMUNICATIONS



(57) Abstract: A data and voice digital communication network installation and networking method, including a plurality of packet communication networking hubs, logically configured in a hierarchy of at least two tiers, a transmission backbone network linking said hubs, including at least one light transmitting fibre with means to extract signals from and apply signals to the fibre which are at least a proportion of end to end signals being carried by the fibre, said signals being extracted to and received from the packet communications networking hubs, at a plurality of selected locations, including at least one which is not located at a primary hub, wherein the logical configuration of a given hub is substantially independent of its physical connectivity to the transmission backbone network.

WO 2005/006657 A1

BEST AVAILABLE COPY